

TC780

Professional Analog Portable Radio

The TC780 is a mid-to-high tier portable radio developed with state-of-the-art analog technology providing a variety of functions. With an Alpha Numeric LCD display and full keypad the radio satisfies the demanding dispatch needs and delivers powerful functions with stable performance and high price-to-performance ratio.



Highlights

- Easy Front Panel Programming
Menu operation and limited keypad access allow you to easily customize parameters and channel settings.
- Power Functions
Power on Self-Test: The radio itself checks the status automatically when powered on, and emits corresponding alert if an error occurs, allowing the user to early detect unit faults
Soft Power Off: After the radio is powered down, it allows some circuits to continue working, and won't need to be reconfigured each time it enters the field
- Safety Features
Lone Worker, Man Down (optional), Emergency Siren, Vibrate, and Safety Check are designed to assure safety in the work place in case of emergency situations.
- HYT HDC2400™ and HDC1200 Signaling
HYT HDC2400™ signaling system allows features including Identification, Calling Timer, Voice Storage, Retrieve Record, Individual Call, Group Call, Broadcast, Stun/Kill & Revive, Status Inquiry, Short Message and Data Transmission.
- Encode & Decode
DTMF and CTCSS / CDCSS Squelch System Encode & Decode.

Features

- Voice Compandor
- MSK Wireless Clone
- PCTuning
- Dual Priority Scan
- Battery Save / Low Battery Alert / Battery Gauge
- Kill / Revive
- Programmable Function Keys
- Talk Around
- Channel Alias
- Programmable Alert Tone
- Auto Acknowledgment
- ATIS
- VOX
- Power-on Password and Data Password
- RSSI (Received Signal Strength Indicator)

Applications

Police



Government



Firefighters

Security



Logistics



Property Management

Accessories

Included

- Li-Ion Battery
- MCU Charger
- Switching Power
- Antenna
- Belt Clip
- Strap

Optional



Earpiece w/on-MIC & PTT
(Transparent Acoustic Tube)
EAN04



MCU Rapid-rate Charger (IS)
(for Li-Ion/Ni-MH Battery)
MCA03



Programming Cable
(USB Port)
PC25



Leather Carrying Case
(Swivel) (Black)
LCBY22

See website for full list

Specifications

General	Frequency Range	VHF: 136-174 MHz ; UHF1: 400 - 470MHz ; UHF2: 450-520MHz
	Channel Capacity	256
	Channel Spacing	25 / 20 / 12.5KHz
	PLL Channel Stepping	5 kHz, 6.25 kHz
	Operating Voltage	7.4V
	RF Power Output	VHF: High 5W - Low 1W UHF: High 4W - Low 1W
	Battery	2100mAh (Li-Ion)
	Battery Life (5-5-90 Duty Cycle,	Approx. 16hrs
	Frequency Stability	± 2.5ppm
	Operating Temperature	-22° F ~ 140° F
	Antenna Impedance	50 Ω
	Dimensions (HxWxD)	4.98 x 2.12 x 1.38 Inches
	Weight	11.99oz
	FCC ID	See website for full list
	Canada Industry ID	See website for full list



Your Local Dealer

For more information, please contact

USAlert, LLC
164 West Royal Palm Road
Boca Raton, FL 33432
Sales: (866) 896-8663
Fax: (561) 394-9986
Web: www.usalertllc.com
Email: info@usalertllc.com

Hytera reserves the right to change product designs or specifications at any time. If you have any questions regarding the accuracy of this information please contact your local sales representative or Hytera directly.

HYT, Hytera are registered trademarks of Hytera Co., Ltd. © 2014 Hytera Co., Ltd. All rights reserved.



Hytera America

Address: 3315 Commerce Parkway
Miramar, Florida 33025, USA
Tel: 800-845-1230 Fax: 954-846-1672
<http://www.hytera.us>
Stock Code: 002583.SZ

