# ALPHA ELITE ™

*POWERED BY UNICATION*

*DISTRIBUTED BY USALERT, LLC*

"a continuation of product and service excellence"

## VHF and 900 FLEX

**SYNTHESIZED**



The all new *Alpha ELITE* pager provides the feature rich messaging capabilities to meet your daily business needs. These easy to use features include multiple message slots, message management, mail drop, zoom and all viewable on a electroluminescent display.

The *Alpha ELITE* is synthesized, fully programmable and available in VHF AND 900 MHz both supporting FLEX coding technology.

- 4 line display or Zoom to 2 line for a larger view ….
- Battery capacity gauge
- UL and CE certifications
- and much more ……

USAlert, LLC
164 West Royal Palm Road
Boca Raton, Florida, 33432-3830
Phone: 561 394 9969

# ALPHA ELITE ™

*POWERED BY* UNICATION
*DISTRIBUTED BY* USALERT, LLC ™

## *Alpha ELITE* Features:

- 32K message memory
- 2025 characters / message
- 5025 characters / mail drop
- Message preview
- Auto EL on
- Message time stamp and message lock
- 8 individual cap codes
- Duplicate message detection
- Notebook entries
- Message retention when off or changing the battery
- Delete individual messages or delete ALL
- 4 lines of text at 80 characters per screen
- Zoom to 2 line view
- Displays time and date
- Electroluminescent display
- Selectable vibrate, various tone alert selections or silent operation
- Reminder alert
- Graphic battery level indication

## *Alpha ELITE* Specifications:

| | |
|---|---|
| Sensitivity | 8  uV/m (1600 BPS) |
| | 11 uV/m (3200 BPS) |
| | 13.5 uV/m (6400 BPS) |
| FLEX | 1600 Baud, 3200 Baud and 6400 Baud |
| Channel spacing | 25 KHz |
| Adjacent channel | 50 dB |
| Image rejection | 50 dB |
| Spurious rejection | 40 dB |
| IM | 40 dB |
| Alert SPL | 75 dB @ 30 cm |
| Operating temperature | -5 C to 40 C |
| Battery | 1.5 Vdc AA |
| Dimensions | 81mm (w) / 55mm (h) / 18.5mm (d) |
| UL rating | Class 1, Division II, Groups A, B, C and D |