

# NP 88 <sup>TM</sup>

"a continuation of product and service excellence"

POWERED BY *UNICATION*  
DISTRIBUTED BY *USALERT, LLC*

## **VHF, UHF and 900 POCSAG**



The all new *NP 88* numeric pager provides the quick messaging capabilities to meet your daily business needs. Compact, lightweight and easy to use.

The *NP 88* is synthesized, fully programmable and available in VHF, UHF and 900 MHz all supporting POCSAG coding technology.

SYNTHESIZED

- Backlight display
- Date and Time
- Low Battery Indication
- and much more .....

USAlert, LLC  
164 West Royal Palm Road  
Boca Raton, Florida, 33432-3830  
Phone: 561 394 9969

Sales: Robert O'Sullivan  
Email: [info@usalertllc.com](mailto:info@usalertllc.com)  
Fax: 561 394 9986  
Web: [www.usalertllc.com](http://www.usalertllc.com)

# NP 88 <sup>TM</sup>

POWERED BY *UNICATION*

DISTRIBUTED BY *USALERT, LLC*

## NP 88 Features:

- Message time stamp and message lock
- 4 individual cap codes
- Duplicate message detection
- Message retention when off or changing the battery
- Delete individual messages or delete ALL
- Displays time and date
- Selectable vibrate, tone alert or silent operation
- Reminder alert
- Low Battery Indication

## NP 88 Specifications:

| Frequency | VHF       | UHF       | 900       |
|-----------|-----------|-----------|-----------|
|           | 137 - 143 | 450 - 460 | 929 - 932 |
|           | 143 - 153 | 460 - 470 |           |
|           | 153 - 163 |           |           |
|           | 163 - 174 |           |           |

|                 |        |
|-----------------|--------|
| Channel Spacing | 25 KHz |
|-----------------|--------|

|             |                        |
|-------------|------------------------|
| Baud Rate   | 512, 1200 and 2400 bps |
| Code Format | POCSAG                 |

| Sensitivity |         |         |         |
|-------------|---------|---------|---------|
| 512 bps     | 5 u/Vm  | 6 u/Vm  | 6 u/Vm  |
| 1200 bps    | 7 u/Vm  | 8 u/Vm  | 8 u/Vm  |
| 2400 bps    | 10 u/Vm | 10 u/Vm | 10 u/Vm |

|                |   |        |
|----------------|---|--------|
| Spur Rejection | >50 dB  | >40 dB |
| Alert SPL      | 78 dB @ 12 inches                             |        |
| Battery Type   | One AAA 1.5 vdc                               |        |
| Dimensions     | 63.65 X 45 X 17.5 mm (2.5 X 1.77 X 0.69 inch) |        |

FEATURES AND SPECIFICATIONS