



NUMERIC MESSAGING
ONE WAY PAGER
NP-88

Great Things Come From Small Packages



Unication Numeric Pager

The NP-88 offers accessibility to stay on top of your busy lifestyle. Perfect for basic wireless communication and user-friendly operation. You can set the pager to generate an audible or a vibration alert no matter under noisy or quiet environments when you are expecting an important page. The NP-88 is compact, lightweight, inexpensive, and the best choice when you need reliable paging with broad coverage.

NUMERIC PAGER

Model Type

NP-88 Numeric Pager FLEX
Synthesized



FEATURE LIST:

DISPLAY:

- * Backlight
In low-light conditions, the backlight makes the screen easy to read.
- * Standby Screen
The standby screen displays the time of day/date or no display.
- * Time of Day and Day/Month
The time of day and the date display whether the pager is on or off.

INDICATORS/ ALERT:

- * Low Battery Indicator
When battery power reaches low levels, low cell is displayed, prompting you to change the battery. All pager alerts change to two seconds in length.
- * Automatic Alert Reset
The pager alerts automatically stop, even if no buttons are pressed.
- * Personal Alarm
This alarm can be set to alert you. The alarm works even when the pager is off.
- * Reminder Alert
The pager chirps or vibrates every two minutes until you read all unread messages.
- * User Selectable Audible Alerts
A selection of five alert tones give you a choice of message alerts heard when you are paged in the audible alert mode D.

MESSAGING:

- * Duplicate Messages
If the same message is received more than once, duplicate sign is displayed at the beginning of the latest message. This message contains the latest timestamp and prevents a repeated message from taking an extra memory slot.
- * Message Erase
Messages can be erased all at once or selectively at your choice to free space in memory.
- * Memory Retention
All messages remain in memory, even when the pager is off and while the battery is being replaced.
- * Memory Capacity
The NP88 FLEX pager can store up to sixteen 20-character messages, for a total of 320 characters.
- * Message Protect
You can protect up to eight messages stored in the pager memory.
- * Overflow
Overflow is displayed when more unread messages are received than the available message memory can hold. After you read all of your unread messages, the standby screen is displayed.
- * Timestamp
The time and the date of a message received are displayed on the screen after each message.

For more information, please contact

USAlert, LLC

164 West Royal Palm Road
Boca Raton, FL 33432
Sales: (866) 896-8663
Fax: (561) 394-9986
Web: www.usalertllc.com
Email: info@usalertllc.com

NP-88

Product Specifications

Band splits	VHF	900 MHz
Frequency Range	137~143MHz 143~153MHz 153~163MHz 163~174MHz	929-932 MHz
Baud Rate (bps)	1600, 3200, 6400	
Code Format	FLEX	
Paging Sensitivity (u/Vm) Best Position Maximum	Baud 1600 : ≤ 8 u/Vm Baud 3200: ≤ 11 u/Vm Baud 6400: ≤ 13.5 u/Vm	
Selectivity	≥ 55 dB	≥ 40 dB
Spurious & Image Rejection	≥ 40 dB	≥ 40 dB
Frequency Stability	$\leq \pm 15$ ppm	$\leq \pm 3.5$ ppm
Channel Spacing	25 kHz	
Receiver Type	Synthesized	
Address Capability	2 FLEX address	
Frequency Deviation	± 4.8 kHz	
Alert Tone	≥ 78 dB @ 12 in (2700 Hz Standard Alert)	
Operating Temperature	5 ° to 40 ° C	
Storage Temperature	-40 ° to +85 ° C	
Power Supply	One 1.5V, AAA Alkaline Battery	
Battery Life (Estimated battery life is based on full battery capacity and 2 pages/day)	Auto Baud Detect Collapse = 4 90days	
Low Battery Alert level	1.2Volts	
Weight with Battery	60g	
Dimensions	63.65 x45.0 x17.5mm (2.50 x1.77 x0.69 in)	



Corporate Headquarters:
Unication Co., Ltd.,
5F., No. 6, Wu-Kung 5Rd., Hsinchuang City,
Taipei, Taiwan. R.O.C.
Phone: + 886 2 2299 9678
Fax: +886 2 2299 7998
Email: salesenquiry@uni.com.tw

Dallas Sales Office:
Unication USA Inc.
1901 E. Lamar Blvd.,
Arlington, TX 76006, U.S.A.
Phone: 817-303-9320
Fax: 817-886-3424
Email: sales@uniamerica.com

www.uni.com.tw

