

FOR ANYTIME ANYWHERE SOLUTIONS

MEDICAL

EMERGENCY

CHILD CARE

HOSPITALITY

ENTERTAINMENT



GEAR STAR

RED ALERT



Alert on the Go

Key Features

Display

LED:

When you are paged, the LED buzzes, beeps or vibrates with red light.

Indicator/Alert

Choices of Alerts:

You can choose between different modes of alerts: Vibrate, Beep and Blink.

Page Alert:

When you receive page, Vibration, beep or LED blink alerts can work at the same time. You can also choose between one or two of the three different modes of alerts at the same time.

Low Battery Indicator:

When battery power reaches low level, red light starts blinking, prompting you to change battery. All pagers alerts change to one second in length.

Stack Charger - Charge All at one go

Max 10:

Maximum 10 sets of Gear Star Pagers can be stacked. And, these pagers can be charged at the same time. Charger will not damage rechargeable batteries by overcharging.

Stack Charger



Specifications [POCSAG/FLEX]

Code Format POCSAG

Band Split

Frequency Range

VHF

137-143 MHz
143-153 MHz
153-163 MHz
163-174 MHz

UHF

450-460 MHz
460-470 MHz

900M

929-932 MHz

Baud Rate (bps)

512/1200/2400 bps

Paging Sensitivity(u/Vm)

512:=-5.7 u/Vm, 1200:=-8u/Vm, 2400:=-10.3u/Vm

Selectivity

=55 dB =50 dB =40 dB

Spurious & Image Rejection

=50dB =50 dB 40 dB

Frequency Stability

+/-15 ppm +/-5 ppm +/-3.5 ppm

Channel Spacing

25 kHz

Receiver Type

Synthesized

Address Capability

6 Pocsag addresses

Frequency Deviation

+/-4.5 kHz

Alert Tone

78 dB@12 in (2730 Hz Standard Alert)

Operating Temperature

0° to 40° C

Power Supply

Sanyo HF-CIU NiMH Rechargeable Battery

Battery Life

(Based on full capacity battery:

24 hrs ON and 8 pages/day)

7 days

Weight with Battery

150g (oz)

Dimensions

Height(25mm)

Diameter(105mm)

Code Format FLEX

Band Split

Frequency Range

VHF

137-143 MHz
143-153 MHz
153-163 MHz
163-174 MHz

900M

929-932 MHz

Baud Rate (bps)

1600/3200/6400 bps

Paging Sensitivity(u/Vm)

1600:=-8u/Vm, 3200:=-11u/Vm, 6400:=-13.5u/Vm

Selectivity

=55 dB =40 dB =40 dB

Spurious & Image Rejection

=40dB =40 dB =40 dB

Frequency Stability

+/-15 ppm +/-5 ppm +/-3.5 ppm

Channel Spacing

25 kHz

Receiver Type

Synthesized

Address Capability

6 FLEX addresses

Frequency Deviation

+/-4.8 kHz

Alert Tone

78 dB@12 in (2730 Hz Standard Alert)

Operating Temperature

0° to 40° C

Power Supply

Sanyo HF-CIU NiMH Rechargeable Battery

Battery Life

(Based on full capacity battery:

24 hrs ON and 8 pages/day)

7 days

Weight with Battery

150g (oz)

Dimensions

Height(25mm)

Diameter(105mm)

For more information, please contact:

USAlert, LLC

164 West Royal Palm Road

Boca Raton, FL 33432

Sales: (866) 896-8663

Fax: (561) 394-9986

Web: www.usalertllc.com

Email: info@usalertllc.com

Charger

Full Recharge Time

8~12 hrs

Electric Current

Max 1500mA

Operating Temperature

0° to 40° C

AC

120V

DC

5V

Adapter

1.5A

Features and specifications subject to change without prior notice.



Unication

©2011 Unication CO., LTD.

The information contained in this document is the exclusive property of Unication CO., LTD.

It shall not be disclosed, distributed or reproduced in whole or in part without written permission of Unication CO., LTD.

Head Office

Unication CO., Ltd.

Tel.: +886-2-2299-9678

Address: 5F., No.6, Wu-Kung 5Rd., Hsinchuang District, New Taipei City, Taiwan

Email: salesenquiry@uni.com.tw

North America Branch Office

Unication USA Inc.

Tel.: +1-817-303-9320

Address: 1901 E. Lamar Blvd., Arlington, TX 76006, U.S.A.

Email: sales@unication.com